

Referencias Bibliográficas

- [1] K. T. V. Grattan, A. T. Augousti, **Introduction to Fiber Optic Sensors**, Chapman & Hall 1996.
- [2] R. Kashyap, **Fiber Bragg Gratings**, Academic Press 1999.
- [3] A. D. Kersey, **Optical Fiber Sensors for Permanent Downwell Monitoring Applications in the Oil and Gas Industry**, IEICE Trans. Electron. E83-C, 3 (2000) pp. 400-404.
- [4] Ph. M. Nellen, P. Mauron, A. Frank, U. Sennhauser, K. Bohnert, P. Pequignot, P. Bodor, H. Brändle, **Reliability of fiber Bragg based sensors for downhole applications**, Sensors and actuators: A 103 (2003) pp. 364-376.
- [5] H-N. Li, D-S. Li, G-B. S., Recent **applications of fiber optic sensors to health monitoring in engineering**, Engineering Structures 26, 11 (2004) pp. 1647-1657.
- [6] E. F. Carome, G Fischer, V. Kubulins, **Fiber-optic sensor system for hydrocarbon vapors**, Sensors and Actuators B: Chemical 13, 1-3 (1993) pp. 305-308.
- [7] O. Kohls, Th. Schepers, **Setup of a fiber optical oxygen multisensor-system and its applications in biotechnology**, Sensors and Actuators B: Chemical 70, 1-3 (2000) pp. 121-130.
- [8] C. During, T. Komeda, M. Matsuto, H. Funakubo, **An optical fibre sensor for use in a tissue cutting tool**, Mechatronics 7, 8 (1997) pp. 701-710.

[9] **17th International Conference on Optical Fiber Sensors 2005**, Bruges, the international society for optical engineering, Bélgica 2005

[10] A. M. B. Braga, L. C. G. Valente, R. D. Regazzi, A. S. Ribeiro, J. L. Arias, R. Munoz, e M. F. Silva Jr., **Transdutor Óptico para Medida Simultânea de Pressão e Temperatura e Método para Dita Medida**, pedido de patente depositado no INPI sob o número: PI0403240-3, 2004.

[11] R. W. A. Llerena, A. M. B. Braga, L. C. G. Valente, J. L. Arias, R. Munoz, e M. F. Silva Jr., **Transdutor de Pressão Diferencial a Fibra Óptica**, pedido de patente depositado no INPI sob o número: PI0403786-3, 2004.

[12] R. W. A. Llerena, **Desenvolvimento de Transdutores a Fibra Óptica para Completão Inteligente de Poços**, Tese de doutorado, Departamento de Engenharia Mecânica, PUC-Rio 2005.

[13] V. R. Jangama, S. Srinivasan, **Calibration of an Integrated Model for Prediction of Corrosivity of CO₂/H₂S Environments**, NACE 1996.

[14] R. Kashyap, **Fiber Bragg Gratings**, Academic Press 1999.

[15] A.Othonos and K.Kalli, **Fiber Bragg Grating: Fundamentals and Applications in telecommunications and sensing**, Artech House, Boston 1999.

[16] A. Dugstad, L. Lunde, **Parametric Study of CO₂ Corrosion of Carbon Steel**, *Corrosion/94*, Paper No.14, Houston, EUA (1994).

[17] D. Brondel, R. Edwards, A. Hayman, D. Hill, S. Mehta, T. Semerad, **Corrosion in the Oil Industry**, Oilfield Review (1994).

[18] O. Hagerup, S. Olsen, **Corrosion control by pH stabiliser, materials and corrosion monitoring in a 160 km multiphase offshore pipeline**, Corrosion/2003, Paper No. 03328, NACE 2003.

- [19] M. F. Da Silva Jr, **Sensor de pH a Fibra Óptica para Monitoramento Permanente em Dutos e Poços de Petróleo**, dissertação de mestrado, Departamento de Engenharia Mecânica, PUC-Rio (2004).
- [20] A. L. C. Triques, D. M. González, J. Celnik, V. G. Schlüter, F. Pereira, A. M. B. Braga, L. C. G. Valente, M. F. Silva Jr, A. R. D'Almeida, M. L. Dias, **Development of pH Sensor for Indirect Evaluation of Pipeline Corrosion**, Proceedings of the X International Congress of the Society for Experimental Mechanics, Costa Mesa (2004).
- [21] V. G. Schlüter, **Development of a Bragg Grating pH Sensor**, trabalho de final de curso, Departamento de Engenharia Mecânica, PUC-Rio (2004).
- [22] A. M. B. Braga, L. C. G. Valente, A. L. C. Triques, A. D. Almeida, F. P. Ribeiro, e M. F. Silva Jr., **Sensor de pH a Fibra Óptica**, pedido de patente depositado no INPI sob o número: PI0404129-1 (2004).
- [23] T. Tanaka, **Gels**, *Scient. Amer.* **244** (1981) pp. **110-123**. , J.Ricka and T.tanaka, **Swelling of Ionic Gels: Quantitative Performance of the Donnan Theory**, Macromolecules (1984)
- [24] R. Bashir, J. Z. Hilt, O. Elibol, A. Gupta, N. A. Peppas, **Micromechanical cantiliver as na ultra sensitive pH microsensor**, vol. 81, no.16, Applied Physics Letters, API 2002.
- [25] F. Jianqi, G. Lixia, **PVA/PAA thermo-crosslinking hydrogel fiber: preparation and pH-sensitive properties in electrolyte solution**, *European Polymer Journal* 38 (2002) pp. 1653-1658.
- [26] S. K. De, Aluru N. R., Johnson B., Crone W. C., Beebe D. J., Moore J., **Equilibrium swelling and kinetics of pH-responsive hydrogels: models, experiments and simulations**, *J. Microelectromech. Syst.* **11**, 5 (2002) pp. 544.

- [27] W. Lee, *Polymer gel based actuator: dynamic model of gel for real time control*, PhD Thesis, Department of Electrical Engineering and Computer Science, M.I.T., (1996).
- [28] Elzubair, A. et al. *Gel fraction measurements in gamma-irradiated ultra high molecular weight polyethylene*. Polymer testing, (2002).
- [29] J. Q. Fei, L. X. Gu, *PVA/PAA Thermo-crosslinking hydrogel fiber: preparation and pH-Sensitive properties in electrolyte solution*, European Polymer Journal **38**, 4706 (2002).
- [30] A. Suzuki, H. Suzuki, *Hysteretic behavior and irreversibility of polymer gels by pH change*, Journal of Chemical Physics **103**, 4706 (1995).
- [31] S. Umemoto, T. Matsumura, T. Sakai, N. Okui, *Elongation/Contraction Properties for Poly(acrylonitrile) Gel Fibers Stimulated by pH*, Polymer Gel and Networks **1**,115 (1993).
- [32] A. Richter, A. Bund, M. Keller, K. Arndt, *Characterization of a microgravimetric sensor based on pH sensitive hydrogels*, Sensors and Actuators **99**, 579 (2004).
- [33] T.Kaneda and Kanbe, **Japan Annual Reviews in Electronics, Computer & Telecommunications**,5,p.45,Ed. Y. Suematsu, OHM-North Holland,1983.
- [34] Handbook of Thin Film Technology, Ed. By L.I Maissel and R. Glang, McGraw Hill,1970.
- [35] Windischmann, **Crit. Rev. Solid State Mater. Sci.** **17**, 1992.
- [36] Cremona, M. **Produção e caracterização física de filmes finos de fluoretos alcalinos para aplicações em dispositivos de guia de onda**. Tese de Doutorado, Departamento de Física, PUC-Rio, 1999.

- [37] I.C. Noyan, J.B. Cohen, "**Residual Stress**" Springer-Verlag, NY – 1987.
- [38] H. Windischmann, Crit. Ver. Solid State Mater. Sci 17 (6) (1992).
- [39] P. H. Townsend e D. M. Barnett; **J. Appl. Phys.** 11(1) (1987)4438-4444.
- [40] A.K. Shinha, H.J. Levinstein, T.E. Smith, **J. Appl. Phys.** 4, 2423 (1978).
- [41] P.A. Flinn et al., **Jornal of physics** 67, 2927 (1990).
- [42] Cremona, M. et al. *In situ hard coating strain measurement using a commercial strain-gage device*, Thin Solid Films, pp.436-440, 2000.
- [43] N. Guyot, Y. Harmand, A. Mézin. *The role of the sample shape and size on the internal stress induced curvature of thin-film substrate systems*, International Journal of Solid and Structures, pp.5143-5154, (2004).
- [44] A. M. B. Braga, L. C. G. Valente, A. L. C. Triques, S.M.M. Quintero. Cremona, M. W. Quirino. **Sensor a fibra óptica para a medida in situ de tensões resudais em filmes finos**, pedido de patente depositado no INPI sob o número: PI0600011-8. 2005.
- [45] S.M.M. Quintero, et al. *Thin film stress measurement by fiber optic strain gage*. **Thin Solid Films**, pp.141-145, 2006
- [46] M.F.Doerner, W.D. Nix, Cri.Rev. Solid state Mater.Sci.14 (3) (1988) 225.
- [47] R.A. Simão. *Magnetron Sputtering SiC films investigates by AFM*, Thin Solid Films, pp.490-494, 2000.
- [48] Costa AK, Camargo SS, Achete CA, et al. *Characterization of ultra-hard silicon carbide coating deposited by RF magnetron sputtering*. Thin Solid Films, pp.243-248, 2000.

- [49] R. Serway. *Physics for scientists and engineers*, Saunders College Publishing, 2000.